

## BLEED OFF SAFLOK COUPLINGS



## TYPE C: COUPLER WITH SMOOTH HOSE SHANK

ND	Inch	For hose mm	Coupler seal	Weight kg	Reference
20	3/4"	19	NBR	0,42	VLCR019DSAFBO
25	1"	25	NBR	0,50	VLCR025DSAFBO
32	1.1/4"	32	NBR	0,76	VLCR032DSAFBO
40	1.1/2"	38	NBR	0,80	VLCR038DSAFBO
50	2"	50	NBR	0,95	VLCR050DSAFBO
65	2.1/2"	63	NBR	1,16	VLCR063DSAFBO
80	3"	75	NBR	1,66	VLCR075DSAFBO
100	4"	100	NBR	2,96	VLCR100DSAFBO



Swivel version: VLCR...DSAF5BO available upon request

## TYPE B: COUPLER MALE THREADED BSPT

ND	Inch	EN 10226-1	Coupler seal	Weight kg	Reference
20	3/4"	R 1/2	NBR	0,39	VLBR019013SAFBO
20	3/4"	R 3/4	NBR	0,40	VLBR019SAFBO
25	1"	R 1	NBR	0,50	VLBR025SAFBO
32	1.1/4"	R 1.1/4	NBR	0,76	VLBR032SAFBO
40	1.1/2"	R 1.1/2	NBR	0,78	VLBR038SAFBO
50	2"	R 2	NBR	0,92	VLBR050SAFBO
65	2.1/2"	R 2.1/2	NBR	1,28	VLBR063SAFBO
80	3"	R 3	NBR	1,65	VLBR075SAFBO
100	4"	R 4	NBR	2,57	VLBR100SAFBO



Coupling standard: Federal Mil-A-A-59326A / DIN 2828

Male thread: EN 10226-1 / DIN 2999-1, BSPT

Stainless steel: AISI 316C / 1.4408

## TYPE B: COUPLER MALE THREADED NPT

ND	Inch	AISI B.1.20.1	Coupler seal	Weight kg	Reference
20	3/4"	NPT 3/4	NBR	0,40	VLBR019NSAFBO
25	1"	NPT 1	NBR	0,50	VLBR025NSAFBO
32	1.1/4"	NPT 1.1/4	NBR	0,76	VLBR032NSAFBO
40	1.1/2"	NPT 1.1/2	NBR	0,78	VLBR038NSAFBO
50	2"	NPT 2	NBR	0,92	VLBR050NSAFBO
65	2.1/2"	NPT 2.1/2	NBR	1,28	VLBR063NSAFBO
80	3"	NPT 3	NBR	1,65	VLBR075NSAFBO
100	4"	NPT 4	NBR	2,57	VLBR100NSAFBO



Coupling standard: Federal Mil-A-A-59326A

Male thread: ANSI B.1.20.1 NPT

Stainless steel: AISI 316C / 1.4408

## BLEED OFF SAFLOK COUPLINGS



## TYPE D: COUPLER DIN 2828 FEMALE THREADED BSP

ND	Inch	EN ISO 228-1	Coupler seal	Weight kg	Reference
20	3/4"	G 1/2	NBR	0,42	VLDR019013DSAFBO
20	3/4"	G 3/4	NBR	0,42	VLDR019DSAFBO
25	1"	G 1	NBR	0,49	VLDR025DSAFBO
32	1.1/4"	G 1.1/4	NBR	0,76	VLDR032DSAFBO
40	1.1/2"	G 1.1/2	NBR	0,85	VLDR038DSAFBO
50	2"	G 2	NBR	0,92	VLDR050DSAFBO
65	2.1/2"	G 2.1/2	NBR	1,17	VLDR063DSAFBO
80	3"	G 3	NBR	1,64	VLDR075DSAFBO
100	4"	G 4	NBR	2,70	VLDR100DSAFBO



Coupling standard: DIN 2828

Female thread: EN ISO 228-1 BSP + PTFE thread seal according to EN 14420-5

Stainless steel: AISI 316C / 1.4408

## TYPE D: COUPLER FEMALE THREADED NPT

ND	Inch	AISI B.1.20.1	Coupler seal	Weight kg	Reference
20	3/4"	NPT 3/4	NBR	0,42	VLDR019NSAFBO
25	1"	NPT 1	NBR	0,49	VLDR025NSAFBO
32	1.1/4"	NPT 1.1/4	NBR	0,76	VLDR032NSAFBO
40	1.1/2"	NPT 1.1/2	NBR	0,85	VLDR038NSAFBO
50	2"	NPT 2	NBR	0,92	VLDR050NSAFBO
65	2.1/2"	NPT 2.1/2	NBR	1,17	VLDR063NSAFBO
80	3"	NPT 3	NBR	1,64	VLDR075NSAFBO
100	4"	NPT 4	NBR	2,70	VLDR100NSAFBO



Coupling standard: Federal Mil A-A-59326A

Female thread: ANSI B.1.20.1 NPT

Stainless steel: AISI 316C / 1.4408

## TYPE DC: COUPLER DUST CAP

ND	Inch	Coupler seal	Weight kg	Reference
20	3/4"	NBR	0,40	VLKR019NSAFBO
25	1"	NBR	0,45	VLKR025NSAFBO
32	1.1/4"	NBR	0,70	VLKR032NSAFBO
40	1.1/2"	NBR	0,72	VLKR038NSAFBO
50	2"	NBR	0,79	VLKR050NSAFBO
65	2.1/2"	NBR	0,97	VLKR063NSAFBO
80	3"	NBR	1,00	VLKR075NSAFBO
100	4"	NBR	2,20	VLKR100NSAFBO



Coupling standard: Federal Mil A-A-59326A

Stainless steel: AISI 316C / 1.4408

# BLEED OFF SAFLOK COUPLINGS



## TYPE DWB: COUPLER BUTT WELD CONNECTION SCH40

ND	Inch	DIN 2828	Coupler seal	Weight kg	Reference
20	3/4"	26,67 x 2,3	NBR	0,40	VLDWBR019S40SAFBO
25	1"	33,40 x 2,6	NBR	0,55	VLDWBR025S40SAFBO
32	1.1/4"	42,16 x 2,6	NBR	0,75	VLDWBR032S40SAFBO
40	1.1/2"	48,26 x 2,6	NBR	0,80	VLDWBR038S40SAFBO
50	2"	60,33 x 2,9	NBR	0,90	VLDWBR050S40SAFBO
65	2.1/2"	76,03 x 2,9	NBR	1,20	VLDWBR063S40SAFBO
80	3"	88,90 x 3,2	NBR	1,60	VLDWBR075S40SAFBO
100	4"	114,30 x 3,6	NBR	2,55	VLDWBR100S40SAFBO



Coupling standard: FederalMil A-A-59326A

Welding end: butt weld for pipe system according to INCH Sch 40S STD

Stainless steel: AISI 316C / 1.4408