

## FEMALE SPUD, HOSE SHANK AND WING NUT

ND	Inch	For hose mm	Material hose shank + nut	Spud material	Weight/pc Kg	Reference
15	1/2"	13	Steel	Steel	0.35	BGFL013
20	3/4"	19	Steel	Steel	0.94	BGFL019
25	1"	25	Steel	Steel	0.82	BGFL025
15	1/2"	13	SS	SS	0.39	BGFL013RR
20	3/4"	19	SS	SS	0.95	BGFL019RR
25	1"	25	SS	SS	0.90	BGFL025RR
15	1/2"	13	SS	Bronze	0.38	BGFL013RB
20	3/4"	19	SS	Bronze	0.99	BGFL019RB
25	1"	25	SS	Bronze	0.92	BGFL025RB



Assembly: RKS steam clamps complying with EN 14423 / DIN 2826

Seal: PTFE +15% graphite

Stainless steel AISI 316 - 1.4401; Zinc plated steel

## WING NUT

ND	Inch	Material	Thread	Weight/pc Kg	Reference
15	1/2"	Steel	NPSM 1"	0.13	BOML013
20	3/4"	Steel	NPSM 1 1/2"	0.33	BOML019
25	1"	Steel	NPSM 1 1/2"	0.33	BOML019
15	1/2"	Stainless steel	NPSM 1"	0.15	BOML013R
20	3/4"	Stainless steel	NPSM 1 1/2"	0.37	BOML019R
25	1"	Stainless steel	NPSM 1 1/2"	0.37	BOML019R



Female thread: NPSM

Stainless steel AISI 316 - 1.4401; Zinc plated steel

## HOSE SHANK

ND	Inch	For hose mm	Material	Weight/pc Kg	Reference
15	1/2"	13	Steel	0.18	BOPL013
20	3/4"	19	Steel	0.20	BOPL019
25	1"	25	Steel	0.25	BOPL025
15	1/2"	13	Stainless steel	0.10	BOPL013R
20	3/4"	19	Stainless steel	0.24	BOPL019R
25	1"	25	Stainless steel	0.25	BOPL025R



Hose shank: EN 14423 / DIN 2826

Assembly: RKS steam clamps complying with EN 14423 / DIN 2826

Stainless steel AISI 316 - 1.4401; Zinc plated steel

## FEMALE SPUD FOR WING NUT

ND	Inch	Material	Male thread	Female thread EN 10226-1	Weight/pc Kg	Reference
15	1/2"	Steel	NPSM 1"	R 1/2"	0.11	BOF013
20	3/4"	Steel	NPSM 1 1/2"	R 3/4"	0.32	BOF019
25	1"	Steel	NPSM 1 1/2"	R 1"	0.25	BOF025
15	1/2"	Stainless steel	NPSM 1"	R 1/2"	0.14	BOF013R
20	3/4"	Stainless steel	NPSM 1 1/2"	R 3/4"	0.34	BOF019R
25	1"	Stainless steel	NPSM 1 1/2"	R 1"	0.28	BOF025R
15	1/2"	Bronze	NPSM 1"	R 1/2"	0.13	BOF013B
20	3/4"	Bronze	NPSM 1 1/2"	R 3/4"	0.38	BOF019B
25	1"	Bronze	NPSM 1 1/2"	R 1"	0.30	BOF025B

Male thread: NPSM  
Female thread: EN 10226-1 / DIN 2999, BSPT  
Seal: PTFE +15% graphite  
Stainless steel AISI 316 - 1.4401; Zinc plated steel



## RKS STEAM CLAMPS EN 14423 / DIN 2826: BRASS

ND	For hose mm	OD hose min-max mm	Material	Height mm	Width mm	Nuts and bolts		Weight kg	Reference
						Quantity	Thread metric		
15	13 x 6	24 - 26	Brass	65	53	4	M6	0.33	RKS013
20	19 x 7	32 - 34	Brass	65	68	4	M8	0.50	RKS019
25	25 x 7.5	39 - 41	Brass	65	77	4	M8	0.58	RKS025

Production method: forged  
Set of RKS steam clamps = one pair of clamps, nuts and bolts included  
Bolts DIN 912 / EN ISO 4762, zinc plated 8.8  
Nuts DIN 934 / EN ISO 4032, zinc plated 8



## RKS STEAM CLAMPS EN 14423 / DIN 2826: STAINLESS STEEL

ND	For hose mm	OD hose min-max mm	Material	Height mm	Width mm	Nuts and bolts		Weight kg	Reference
						Quantity	Thread metric		
13	13 x 6	24 - 26	SS	65	53	4	M6	0.31	RKSR013
20	19 x 7	32 - 34	SS	65	68	4	M8	0.46	RKSR019
25	25 x 7.5	39 - 41	SS	65	77	4	M8	0.53	RKSR025

Production method: investment casting  
Set of RKS steam clamps = one pair of clamps, nuts and bolts included  
Bolts DIN 912 / EN ISO 4762, stainless steel A.2  
Nuts DIN 934 / EN ISO 4032, stainless steel A.2

