

## EXPRESS COUPLINGS



## EXPRESS COUPLING MALE THREADED

ND	Inch	Thread EN ISO 228-1	Material	Weight/pc Kg	Reference
6	1/4"	G 1/4	Brass	0.09	EXM006
10	3/8"	G 3/8	Brass	0.10	EXM010
15	1/2"	G 1/2	Brass	0.10	EXM013
20	3/4"	G 3/4	Brass	0.10	EXM019
25	1"	G 1	Brass	0.14	EXM025
32	1.1/4"	G 1.1/4	Brass	0.25	EXM032
10	3/8"	G 3/8	Stainless steel	0.10	EXMR010
15	1/2"	G 1/2	Stainless steel	0.10	EXMR013
20	3/4"	G 3/4	Stainless steel	0.10	EXMR019
25	1"	G 1	Stainless steel	0.25	EXMR025



Claw distance: 41 mm  
 Working pressure: 10 bar / 145 psi  
 Profiled seal: NBR (standard) for brass version  
                   FPM for stainless steel version  
 Stainless steel: AISI 316 / 1.4401  
 Male thread EN ISO 228-1, BSP

## EXPRESS COUPLING FEMALE THREADED

ND	Inch	Thread EN ISO 228-1	Material	Weight/pc Kg	Reference
6	1/4"	G 1/4	Brass	0.09	EXF006
10	3/8"	G 3/8	Brass	0.10	EXF010
15	1/2"	G 1/2	Brass	0.10	EXF013
20	3/4"	G 3/4	Brass	0.11	EXF019
25	1"	G 1	Brass	0.11	EXF025
32	1.1/4"	G 1.1/4	Brass	0.25	EXF032
10	3/8"	G 3/8	Stainless steel	0.10	EXFR010
15	1/2"	G 1/2	Stainless steel	0.10	EXFR013
20	3/4"	G 3/4	Stainless steel	0.11	EXFR019
25	1"	G 1	Stainless steel	0.25	EXFR025



Claw distance: 41 mm  
 Working pressure: 10 bar / 145 psi  
 Profiled seal: NBR (standard) for brass version  
                   FPM for stainless steel version  
 Stainless steel: AISI 316 / 1.4401  
 Female thread EN ISO 228-1, BSP

## EXPRESS COUPLINGS



## EXPRESS COUPLING WITH SERRATED HOSE SHANK

ND	Inch	For hose mm	Material	Weight/pc Kg	Reference
6	1/4"	6	Brass	0.10	EXS006
10	3/8"	10	Brass	0.12	EXS010
13	1/2"	13	Brass	0.12	EXS013
16	5/8"	16	Brass	0.13	EXS016
20	3/4"	20	Brass	0.13	EXS020
25	1"	25	Brass	0.15	EXS025
13	1/2"	13	Stainless steel	0.11	EXSR013
16	5/8"	16	Stainless steel	0.12	EXSR016
20	3/4"	20	Stainless steel	0.13	EXSR019
25	1"	25	Stainless steel	0.16	EXSR025



Claw distance: 41 mm  
 Working pressure: 10 bar / 145 psi  
 Profiled seal: NBR (standard) for brass version  
                   FPM for stainless steel version  
 Assembly: worm drive clamps  
 Stainless steel: AISI 316 / 1.4401

## CLAMPS

Material	Outside hose min-max mm	Weight/pc Kg	Reference
Carbon steel	19-21	0.04	EXK019
Carbon steel	22-25	0.04	EXK022
Carbon steel	25-27	0.06	EXK025
Carbon steel	28-30	0.06	EXK028
Carbon steel	31-33	0.08	EXK031
Carbon steel	34-36	0.13	EXK034
Carbon steel	37-39	0.15	EXK037



## EXPRESS COUPLING CAP

Material	Weight/pc Kg	Reference
Brass	0.13	EXK
Stainless steel	0.13	EXKR



Claw distance: 41 mm  
 Working pressure: 10 bar / 145 psi  
 Profiled seal: NBR (standard) for brass version  
                   FPM for stainless steel version  
 Cap without chain  
 Stainless steel: AISI 316 / 1.4401

## EXPRESS COUPLINGS


**PROFILED SEAL**

Material	Colour	OD Ø mm	ID Ø mm	Height +0,5 mm	Box pieces	Weight kg	Reference
NBR	black	35.0	15.0	10.0	50	0.01	EXX
FPM	green	35.0	15.0	10.0	50	0.01	EXXV

