

FLANGE COUPLINGS



SWIVEL FLANGE COUPLING WITH SMOOTH HOSE SHANK

ND	Inch	Flange pressure class	For hose mm	Material hose shank	Flange material	Weight/pc kg	Reference
15	1/2"	EN-DIN PN 25/40	13	Steel	Steel	0.82	FLG013
20	3/4"	EN-DIN PN 25/40	19	Steel	Steel	1.12	FLG019
25	1"	EN-DIN PN 25/40	25	Steel	Steel	1.56	FLG025
32	1.1/4"	EN-DIN PN 25/40	32	Steel	Steel	2.10	FLG032
40	1.1/2"	EN-DIN PN 25/40	38	Steel	Steel	2.65	FLG038
40	1.1/2"	EN-DIN PN 25/40	40	Steel	Steel	2.65	FLG040*
50	2"	EN-DIN PN 10/16	50	Steel	Steel	3.22	FLG050
65	2.1/2"	EN-DIN PN 10/16	63	Steel	Steel	4.45	FLG063
65	2.1/2"	EN-DIN PN 10/16	65	Steel	Steel	4.45	FLG065*
80	3"	EN-DIN PN 10/16	75	Steel	Steel	5.54	FLG075
80	3"	EN-DIN PN 10/16	80	Steel	Steel	5.60	FLG080*
100	4"	EN-DIN PN 10/16	100	Steel	Steel	6.73	FLG100
125	5"	EN-DIN PN 10/16	125	Steel	Steel	9.61	FLG125
150	6"	EN-DIN PN 10/16	150	Steel	Steel	12.34	FLG150
200	8"	EN-DIN PN 10	200	Steel	Steel	18.55	FLG200PN10*
200	8"	EN-DIN PN 16	200	Steel	Steel	18.00	FLG200PN16

15	1/2"	EN-DIN PN 25/40	13	SS	SS	0.81	RRFLG013
20	3/4"	EN-DIN PN 25/40	19	SS	SS	1.11	RRFLG019
25	1"	EN-DIN PN 25/40	25	SS	SS	1.50	RRFLG025
32	1.1/4"	EN-DIN PN 25/40	32	SS	SS	2.19	RRFLG032
40	1.1/2"	EN-DIN PN 25/40	38	SS	SS	2.68	RRFLG038
40	1.1/2"	EN-DIN PN 25/40	40	SS	SS	2.68	RRFLG040*
50	2"	EN-DIN PN 10/16	50	SS	SS	3.58	RRFLG050
65	2.1/2"	EN-DIN PN 10/16	63	SS	SS	4.18	RRFLG063
65	2.1/2"	EN-DIN PN 10/16	65	SS	SS	4.45	RRFLG065*
80	3"	EN-DIN PN 10/16	75	SS	SS	5.43	RRFLG075
80	3"	EN-DIN PN 10/16	80	SS	SS	5.54	RRFLG080*
100	4"	EN-DIN PN 10/16	100	SS	SS	6.89	RRFLG100
125	5"	EN-DIN PN 10/16	125	SS	SS	9.13	RRFLG125
150	6"	EN-DIN PN 10/16	150	SS	SS	12.44	RRFLG150

15	1/2"	EN-DIN PN 25/40	13	PP	Steel	0.66	PSFLG013
20	3/4"	EN-DIN PN 25/40	19	PP	Steel	0.81	PSFLG019
25	1"	EN-DIN PN 25/40	25	PP	Steel	1.07	PSFLG025
32	1.1/4"	EN-DIN PN 25/40	32	PP	Steel	1.41	PSFLG032
40	1.1/2"	EN-DIN PN 25/40	38	PP	Steel	1.85	PSFLG038
40	1.1/2"	EN-DIN PN 25/40	40	PP	Steel	1.85	PSFLG040*
50	2"	EN-DIN PN 10/16	50	PP	Steel	2.00	PSFLG050
65	2.1/2"	EN-DIN PN 10/16	63	PP	Steel	2.69	PSFLG063
65	2.1/2"	EN-DIN PN 10/16	65	PP	Steel	2.8	PSFLG065*
80	3"	EN-DIN PN 10/16	75	PP	Steel	3.52	PSFLG075
80	3"	EN-DIN PN 10/16	80	PP	Steel	3.52	PSFLG080*
100	4"	EN-DIN PN 10/16	100	PP	Steel	4.00	PSFLG100

15	1/2"	EN-DIN PN 25/40	13	SS	Steel	0.81	RSFLG013
20	3/4"	EN-DIN PN 25/40	19	SS	Steel	1.11	RSFLG019
25	1"	EN-DIN PN 25/40	25	SS	Steel	1.49	RSFLG025
32	1.1/4"	EN-DIN PN 25/40	32	SS	Steel	2.16	RSFLG032
40	1.1/2"	EN-DIN PN 25/40	38	SS	Steel	2.70	RSFLG038
40	1.1/2"	EN-DIN PN 25/40	40	SS	Steel	2.70	RSFLG040*
50	2"	EN-DIN PN 10/16	50	SS	Steel	3.26	RSFLG050
65	2.1/2"	EN-DIN PN 10/16	63	SS	Steel	4.28	RSFLG063
65	2.1/2"	EN-DIN PN 10/16	65	SS	Steel	4.28	RSFLG065*
80	3"	EN-DIN PN 10/16	75	SS	Steel	5.52	RSFLG075
80	3"	EN-DIN PN 10/16	80	SS	Steel	5.52	RSFLG080*
100	4"	EN-DIN PN 10/16	100	SS	Steel	7.01	RSFLG100
150	6"	EN-DIN PN 10/16	150	SS	Steel	12.49	RSFLG150

*available on request



FLANGE COUPLINGS



SWIVEL FLANGE COUPLING WITH SMOOTH HOSE SHANK

ND	Inch	Flange pressure class	For hose mm	Material hose shank	Flange material	Weight/pc kg	Reference
15	1/2"	EN 1092-1-PN 40	13	Steel	Steel	0.92	FLGP4013
20	3/4"	EN 1092-1-PN 40	19	Steel	Steel	1.17	FLGP4019
25	1"	EN 1092-1-PN 40	25	Steel	Steel	1.94	FLGP4025
32	1.1/4"	EN 1092-1-PN 40	32	Steel	Steel	2.82	FLGP4032
40	1.1/2"	EN 1092-1-PN 40	38	Steel	Steel	3.28	FLGP4038
50	2"	EN 1092-1-PN 40	50	Steel	Steel	4.61	FLGP4050
65	2.1/2"	EN 1092-1-PN 40	63	Steel	Steel	6.16	FLGP4063
80	3"	EN 1092-1-PN 40	75	Steel	Steel	8.33	FLGP4075
100	4"	EN 1092-1-PN 40	100	Steel	Steel	9.88	FLGP4100

15	1/2"	EN 1092-1-PN 40	13	SS	SS	1.01	RRFLGP4013
20	3/4"	EN 1092-1-PN 40	19	SS	SS	1.61	RRFLGP4019
25	1"	EN 1092-1-PN 40	25	SS	SS	1.87	RRFLGP4025
32	1.1/4"	EN 1092-1-PN 40	32	SS	SS	2.78	RRFLGP4032
40	1.1/2"	EN 1092-1-PN 40	38	SS	SS	3.33	RRFLGP4038
50	2"	EN 1092-1-PN 40	50	SS	SS	4.65	RRFLGP4050
65	2.1/2"	EN 1092-1-PN 40	63	SS	SS	6.17	RRFLGP4063
80	3"	EN 1092-1-PN 40	75	SS	SS	8.31	RRFLGP4075
100	4"	EN 1092-1-PN 40	100	SS	SS	9.58	RRFLGP4100

15	1/2"	ASTM 150 lbs	13	Steel	Steel	0.59	FLGA1013
20	3/4"	ASTM 150 lbs	19	Steel	Steel	0.92	FLGA1019
25	1"	ASTM 150 lbs	25	Steel	Steel	1.34	FLGA1025
32	1.1/4"	ASTM 150 lbs	32	Steel	Steel	1.82	FLGA1032
40	1.1/2"	ASTM 150 lbs	38	Steel	Steel	2.25	FLGA1038
40	1.1/2"	ASTM 150 lbs	40	Steel	Steel	2.25	FLGA1040*
50	2"	ASTM 150 lbs	50	Steel	Steel	3.47	FLGA1050
65	2.1/2"	ASTM 150 lbs	63	Steel	Steel	5.68	FLGA1063
65	2.1/2"	ASTM 150 lbs	65	Steel	Steel	5.68	FLGA1065*
80	3"	ASTM 150 lbs	75	Steel	Steel	6.30	FLGA1075
80	3"	ASTM 150 lbs	80	Steel	Steel	6.30	FLGA1080*
100	4"	ASTM 150 lbs	100	Steel	Steel	8.83	FLGA1100
125	5"	ASTM 150 lbs	125	Steel	Steel	12.34	FLGA1125
150	6"	ASTM 150 lbs	150	Steel	Steel	15.34	FLGA1150

15	1/2"	ASTM 150 lbs	13	SS	SS	0.60	RRFLGA1013
20	3/4"	ASTM 150 lbs	19	SS	SS	1.07	RRFLGA1019
25	1"	ASTM 150 lbs	25	SS	SS	1.29	RRFLGA1025
32	1.1/4"	ASTM 150 lbs	32	SS	SS	1.95	RRFLGA1032
40	1.1/2"	ASTM 150 lbs	38	SS	SS	2.38	RRFLGA1038
40	1.1/2"	ASTM 150 lbs	40	SS	SS	2.38	RRFLGA1040*
50	2"	ASTM 150 lbs	50	SS	SS	3.65	RRFLGA1050
65	2.1/2"	ASTM 150 lbs	63	SS	SS	5.38	RRFLGA1063
65	2.1/2"	ASTM 150 lbs	65	SS	SS	5.38	RRFLGA1065*
80	3"	ASTM 150 lbs	75	SS	SS	6.23	RRFLGA1075
80	3"	ASTM 150 lbs	80	SS	SS	6.23	RRFLGA1080*
100	4"	ASTM 150 lbs	100	SS	SS	7.55	RRFLGA1100
125	5"	ASTM 150 lbs	125	SS	SS	11.74	RRFLGA1125
150	6"	ASTM 150 lbs	150	SS	SS	15.94	RRFLGA1150

Swivel flange: EN 1092-1 / type 04
ASTM / A 182/ ANSI B16.5, ASA 150 lbs

Assembly: RK and RKP safety clamps complying with EN 14420-3 / DIN 2817, FLEXOLINE® safety clamps
SS = Stainless steel AISI 316 - 1.4401 / Steel = galvanized steel / PP = Polypropylene

* available on request



FLANGE COUPLINGS



FIXED FLANGE COUPLING WITH SMOOTH HOSE SHANK

ND	Inch	Flange pressure class	For hose mm	Material	Weight/pc kg	Reference
15	1/2"	EN 1092-1-PN 40	13	Steel	0.69	FVG013
20	3/4"	EN 1092-1-PN 40	19	Steel	1.00	FVG019
25	1"	EN 1092-1-PN 40	25	Steel	1.23	FVG025
32	1.1/4"	EN 1092-1-PN 40	32	Steel	1.80	FVG032
40	1.1/2"	EN 1092-1-PN 40	38	Steel	2.01	FVG038
40	1.1/2"	EN 1092-1-PN 40	40	Steel	2.01	FVG040*
50	2"	EN 1092-1-PN 40	50	Steel	2.80	FVG050
65	2.1/2"	EN 1092-1-PN 40	63	Steel	3.47	FVG063
65	2.1/2"	EN 1092-1-PN 40	65	Steel	3.47	FVG065*
80	3"	EN 1092-1-PN 40	75	Steel	4.26	FVG075
80	3"	EN 1092-1-PN 40	80	Steel	4.26	FVG080*
100	4"	EN 1092-1-PN 40	100	Steel	5.67	FVG100
125	5"	EN 1092-1-PN 40	125	Steel	8.73	FVG125
150	6"	EN 1092-1-PN 40	150	Steel	11.64	FVG150
200	8"	EN 1092-1-PN 40	200	Steel	17.89	FVG200
15	1/2"	EN 1092-1-PN 40	13	SS	0.70	RFVG013
20	3/4"	EN 1092-1-PN 40	19	SS	1.01	RFVG019
25	1"	EN 1092-1-PN 40	25	SS	1.24	RFVG025
32	1.1/4"	EN 1092-1-PN 40	32	SS	1.83	RFVG032
40	1.1/2"	EN 1092-1-PN 40	38	SS	2.03	RFVG038
40	1.1/2"	EN 1092-1-PN 40	40	SS	2.03	RFVG040*
50	2"	EN 1092-1-PN 40	50	SS	2.79	RFVG050
65	2.1/2"	EN 1092-1-PN 40	63	SS	3.47	RFVG063
65	2.1/2"	EN 1092-1-PN 40	65	SS	3.47	RFVG065*
80	3"	EN 1092-1-PN 40	75	SS	4.33	RFVG075
80	3"	EN 1092-1-PN 40	80	SS	4.33	RFVG080*
100	4"	EN 1092-1-PN 40	100	SS	5.67	RFVG100
125	5"	EN 1092-1-PN 40	125	SS	8.63	RFVG125
150	6"	EN 1092-1-PN 40	150	SS	11.99	RFVG150
15	1/2"	EN 1092-1-PN 40	13	Steel	0.78	FVGP4013
20	3/4"	EN 1092-1-PN 40	19	Steel	1.11	FVGP4019
25	1"	EN 1092-1-PN 40	25	Steel	1.38	FVGP4025
32	1.1/4"	EN 1092-1-PN 40	32	Steel	1.99	FVGP4032
40	1.1/2"	EN 1092-1-PN 40	38	Steel	2.48	FVGP4038
40	1.1/2"	EN 1092-1-PN 40	40	Steel	2.48	FVGP4040*
50	2"	EN 1092-1-PN 40	50	Steel	3.09	FVGP4050
65	2.1/2"	EN 1092-1-PN 40	63	Steel	4.12	FVGP4063
65	2.1/2"	EN 1092-1-PN 40	65	Steel	4.12	FVGP4065*
80	3"	EN 1092-1-PN 40	75	Steel	5.31	FVGP4075
80	3"	EN 1092-1-PN 40	80	Steel	5.31	FVGP4080*
100	4"	EN 1092-1-PN 40	100	Steel	7.57	FVGP4100
125	5"	EN 1092-1-PN 40	125	Steel	11.50	FVGP4125
150	6"	EN 1092-1-PN 40	150	Steel	15.69	FVGP4150
15	1/2"	EN 1092-1-PN 40	13	SS	0.80	RFVGP4013
20	3/4"	EN 1092-1-PN 40	19	SS	1.12	RFVGP4019
25	1"	EN 1092-1-PN 40	25	SS	1.39	RFVGP4025
32	1.1/4"	EN 1092-1-PN 40	32	SS	2.02	RFVGP4032
40	1.1/2"	EN 1092-1-PN 40	38	SS	2.50	RFVGP4038
40	1.1/2"	EN 1092-1-PN 40	40	SS	2.50	RFVGP4040*
50	2"	EN 1092-1-PN 40	50	SS	3.08	RFVGP4050
65	2.1/2"	EN 1092-1-PN 40	63	SS	4.15	RFVGP4063
65	2.1/2"	EN 1092-1-PN 40	65	SS	4.15	RFVGP4065*
80	3"	EN 1092-1-PN 40	75	SS	5.38	RFVGP4075
80	3"	EN 1092-1-PN 40	80	SS	5.38	RFVGP4080*
100	4"	EN 1092-1-PN 40	100	SS	7.57	RFVGP4100
125	5"	EN 1092-1-PN 40	125	SS	11.40	RFVGP4125
150	6"	EN 1092-1-PN 40	150	SS	16.04	RFVGP4150



FIXED FLANGE COUPLING WITH SMOOTH HOSE SHANK

ND	Inch	Flange pressure class	For hose mm	Material	Weight/pc kg	Reference
15	1/2"	ASTM 150 lbs	13	Steel	0.52	FVGA1013
20	3/4"	ASTM 150 lbs	19	Steel	0.76	FVGA1019
25	1"	ASTM 150 lbs	25	Steel	1.10	FVGA1025
32	1.1/4"	ASTM 150 lbs	32	Steel	1.44	FVGA1032
40	1.1/2"	ASTM 150 lbs	38	Steel	1.87	FVGA1038
40	1.1/2"	ASTM 150 lbs	40	Steel	1.87	FVGA1040*
50	2"	ASTM 150 lbs	50	Steel	2.85	FVGA1050
65	2.1/2"	ASTM 150 lbs	63	Steel	4.52	FVGA1063
65	2.1/2"	ASTM 150 lbs	65	Steel	4.52	FVGA1065*
80	3"	ASTM 150 lbs	75	Steel	5.48	FVGA1075
80	3"	ASTM 150 lbs	80	Steel	5.48	FVGA1080*
100	4"	ASTM 150 lbs	100	Steel	7.89	FVGA1100
125	5"	ASTM 150 lbs	125	Steel	10.99	FVGA1125
150	6"	ASTM 150 lbs	150	Steel	14.49	FVGA1150

15	1/2"	ASTM 150 lbs	13	SS	0.75	RFVGA1013
20	3/4"	ASTM 150 lbs	19	SS	0.86	RFVGA1019
25	1"	ASTM 150 lbs	25	SS	1.20	RFVGA1025
32	1.1/4"	ASTM 150 lbs	32	SS	1.64	RFVGA1032
40	1.1/2"	ASTM 150 lbs	38	SS	1.97	RFVGA1038
40	1.1/2"	ASTM 150 lbs	40	SS	1.97	RFVGA1040*
50	2"	ASTM 150 lbs	50	SS	2.96	RFVGA1050
65	2.1/2"	ASTM 150 lbs	63	SS	4.81	RFVGA1063
65	2.1/2"	ASTM 150 lbs	65	SS	4.81	RFVGA1065*
80	3"	ASTM 150 lbs	75	SS	5.83	RFVGA1075
80	3"	ASTM 150 lbs	80	SS	5.83	RFVGA1080*
100	4"	ASTM 150 lbs	100	SS	8.55	RFVGA1100
125	5"	ASTM 150 lbs	125	SS	11.53	RFVGA1125
150	6"	ASTM 150 lbs	150	SS	15.24	RFVGA1150



Fixed flange: EN 1092-1 / type 11

ASTM / A 182/ ANSI B16.5, ASA 150 lbs

Assembly: RK and RKP safety clamps complying with EN 14420-3 / DIN 2817, FLEXOLINE® safety clamps

SS = Stainless steel AISI 316 - 1.4401

Steel = galvanized steel

FLANGE COUPLINGS



SWIVEL FLANGE COUPLING WITH SERRATED HOSE SHANK AND COLLAR

ND	Inch	Flange pressure class	For hose mm	Material hose shank	Flange material	Weight/pc kg	Reference
15	1/2"	EN 1092-1-PN40	13	Steel	Steel	0.82	FLP013
20	3/4"	EN 1092-1-PN40	19	Steel	Steel	1.10	FLP019
25	1"	EN 1092-1-PN40	25	Steel	Steel	1.53	FLP025
32	1.1/4"	EN 1092-1-PN40	32	Steel	Steel	2.06	FLP032
40	1.1/2"	EN 1092-1-PN40	38	Steel	Steel	2.68	FLP038
40	1.1/2"	EN 1092-1-PN40	40	Steel	Steel	2.68	FLP040*
50	2"	EN 1092-1-PN40	50	Steel	Steel	3.22	FLP050
65	2.1/2"	EN 1092-1-PN40	63	Steel	Steel	4.18	FLP063
65	2.1/2"	EN 1092-1-PN40	65	Steel	Steel	4.18	FLP065*
80	3"	EN 1092-1-PN40	75	Steel	Steel	5.29	FLP075
80	3"	EN 1092-1-PN40	80	Steel	Steel	5.29	FLP080*
100	4"	EN 1092-1-PN40	100	Steel	Steel	7.01	FLP100
125	5"	EN 1092-1-PN40	125	Steel	Steel	14.19	FLP125
150	6"	EN 1092-1-PN40	150	Steel	Steel	17.72	FLP150
200	8"	EN 1092-1-PN40	200	Steel	Steel	20.0	FLP200PN10*
200	8"	EN 1092-1-PN40	200	Steel	Steel	22.6	FLP200PN16

15	1/2"	EN 1092-1-PN40	13	SS	SS	0.79	RRFLP013
20	3/4"	EN 1092-1-PN40	19	SS	SS	1.10	RRFLP019
25	1"	EN 1092-1-PN40	25	SS	SS	1.49	RRFLP025
32	1.1/4"	EN 1092-1-PN40	32	SS	SS	2.12	RRFLP032
40	1.1/2"	EN 1092-1-PN40	38	SS	SS	2.50	RRFLP038
40	1.1/2"	EN 1092-1-PN40	40	SS	SS	2.50	RRFLP040*
50	2"	EN 1092-1-PN40	50	SS	SS	3.43	RRFLP050
65	2.1/2"	EN 1092-1-PN40	63	SS	SS	3.85	RRFLP063
65	2.1/2"	EN 1092-1-PN40	65	SS	SS	3.85	RRFLP065*
80	3"	EN 1092-1-PN40	75	SS	SS	5.25	RRFLP075
80	3"	EN 1092-1-PN40	80	SS	SS	5.25	RRFLP080*
100	4"	EN 1092-1-PN40	100	SS	SS	6.02	RRFLP100
125	5"	EN 1092-1-PN40	125	SS	SS	9.13	RRFLP125
150	6"	EN 1092-1-PN40	150	SS	SS	11.83	RRFLP150

15	1/2"	EN 1092-1-PN40	13	SS	Steel	0.82	RSFLP013
20	3/4"	EN 1092-1-PN40	19	SS	Steel	1.12	RSFLP019
25	1"	EN 1092-1-PN40	25	SS	Steel	1.53	RSFLP025
32	1.1/4"	EN 1092-1-PN40	32	SS	Steel	1.99	RSFLP032
40	1.1/2"	EN 1092-1-PN40	38	SS	Steel	2.52	RSFLP038
40	1.1/2"	EN 1092-1-PN40	40	SS	Steel	2.52	RSFLP040*
50	2"	EN 1092-1-PN40	50	SS	Steel	3.11	RSFLP050
65	2.1/2"	EN 1092-1-PN40	63	SS	Steel	3.95	RSFLP063
65	2.1/2"	EN 1092-1-PN40	65	SS	Steel	3.95	RSFLP065*
80	3"	EN 1092-1-PN40	75	SS	Steel	5.34	RSFLP075
80	3"	EN 1092-1-PN40	80	SS	Steel	5.34	RSFLP080*
100	4"	EN 1092-1-PN40	100	SS	Steel	6.14	RSFLP100
125	5"	EN 1092-1-PN40	125	SS	Steel	9.01	RSFLP125
150	6"	EN 1092-1-PN40	150	SS	Steel	11.68	RSFLP150



SWIVEL FLANGE COUPLING WITH SERRATED HOSE SHANK AND COLLAR

ND	Inch	Flange pressure class	For hose mm	Material hose shank	Flange material	Weight/pc kg	Reference
15	1/2"	ASTM 150 lbs	13	Steel	Steel	0.57	FLPA1013
20	3/4"	ASTM 150 lbs	19	Steel	Steel	0.90	FLPA1019
25	1"	ASTM 150 lbs	25	Steel	Steel	1.31	FLPA1025
32	1.1/4"	ASTM 150 lbs	32	Steel	Steel	1.78	FLPA1032
40	1.1/2"	ASTM 150 lbs	38	Steel	Steel	2.28	FLPA1038
40	1.1/2"	ASTM 150 lbs	40	Steel	Steel	2.28	FLPA1040*
50	2"	ASTM 150 lbs	50	Steel	Steel	3.47	FLPA1050
65	2.1/2"	ASTM 150 lbs	63	Steel	Steel	5.34	FLPA1063
65	2.1/2"	ASTM 150 lbs	65	Steel	Steel	5.34	FLPA1065*
80	3"	ASTM 150 lbs	75	Steel	Steel	6.05	FLPA1075
80	3"	ASTM 150 lbs	80	Steel	Steel	6.05	FLPA1080*
100	4"	ASTM 150 lbs	100	Steel	Steel	9.11	FLPA1100
125	5"	ASTM 150 lbs	125	Steel	Steel	16.49	FLPA1125
150	6"	ASTM 150 lbs	150	Steel	Steel	20.72	FLPA1150



15	1/2"	ASTM 150 lbs	13	SS	SS	0.79	RRFLPA1013
20	3/4"	ASTM 150 lbs	19	SS	SS	1.10	RRFLPA1019
25	1"	ASTM 150 lbs	25	SS	SS	1.50	RRFLPA1025
32	1.1/4"	ASTM 150 lbs	32	SS	SS	2.12	RRFLPA1032
40	1.1/2"	ASTM 150 lbs	38	SS	SS	2.50	RRFLPA1038
40	1.1/2"	ASTM 150 lbs	40	SS	SS	2.50	RRFLPA1040*
50	2"	ASTM 150 lbs	50	SS	SS	3.43	RRFLPA1050
65	2.1/2"	ASTM 150 lbs	63	SS	SS	3.85	RRFLPA1063
65	2.1/2"	ASTM 150 lbs	65	SS	SS	3.85	RRFLPA1065*
80	3"	ASTM 150 lbs	75	SS	SS	5.25	RRFLPA1075
80	3"	ASTM 150 lbs	80	SS	SS	5.25	RRFLPA1080*
100	4"	ASTM 150 lbs	100	SS	SS	6.02	RRFLPA1100
125	5"	ASTM 150 lbs	125	SS	SS	11.74	RRFLPA1125
150	6"	ASTM 150 lbs	150	SS	SS	15.33	RRFLPA1150



Swivel flange: EN 1092-1 / type 04
 ASTM / A 182/ ANSI B16.5, ASA 150 lbs
 Assembly: HRRK swage ferrules, worm drive and band clamps
 SS = Stainless steel AISI 316 - 1.4401
 Steel = galvanized steel
 Polypropylene flange available on request
 *Available on request

FLANGE COUPLINGS



FIXED FLANGE COUPLING WITH SERRATED HOSE SHANK AND COLLAR

ND	Inch	Flange pressure class	For hose mm	Material	Weight/pc kg	Reference
15	1/2"	EN 1092-1-PN40	13	Steel	0.70	FVP013
20	3/4"	EN 1092-1-PN40	19	Steel	1.02	FVP019
25	1"	EN 1092-1-PN40	25	Steel	1.23	FVP025
32	1.1/4"	EN 1092-1-PN40	32	Steel	1.82	FVP032
40	1.1/2"	EN 1092-1-PN40	38	Steel	2.01	FVP038
40	1.1/2"	EN 1092-1-PN40	40	Steel	2.01	FVP040*
50	2"	EN 1092-1-PN40	50	Steel	2.79	FVP050
65	2.1/2"	EN 1092-1-PN40	63	Steel	3.70	FVP063
65	2.1/2"	EN 1092-1-PN40	65	Steel	3.70	FVP065*
80	3"	EN 1092-1-PN40	75	Steel	4.26	FVP075
80	3"	EN 1092-1-PN40	80	Steel	4.26	FVP080*
100	4"	EN 1092-1-PN40	100	Steel	5.68	FVP100
125	5"	EN 1092-1-PN40	125	Steel	8.51	FVP125
150	6"	EN 1092-1-PN40	150	Steel	11.29	FVP150
200	8"	EN 1092-1-PN40	200	Steel	17.44	FVP200PN10*
200	8"	EN 1092-1-PN40	200	Steel	17.44	FVP200PN16

15	1/2"	EN 1092-1-PN40	13	SS	0.70	RFVP013
20	3/4"	EN 1092-1-PN40	19	SS	1.01	RFVP019
25	1"	EN 1092-1-PN40	25	SS	1.24	RFVP025
32	1.1/4"	EN 1092-1-PN40	32	SS	1.83	RFVP032
40	1.1/2"	EN 1092-1-PN40	38	SS	2.03	RFVP038
40	1.1/2"	EN 1092-1-PN40	40	SS	2.03	RFVP040*
50	2"	EN 1092-1-PN40	50	SS	2.79	RFVP050
65	2.1/2"	EN 1092-1-PN40	63	SS	3.47	RFVP063
65	2.1/2"	EN 1092-1-PN40	65	SS	3.47	RFVP065*
80	3"	EN 1092-1-PN40	75	SS	4.33	RFVP075
80	3"	EN 1092-1-PN40	80	SS	4.33	RFVP080*
100	4"	EN 1092-1-PN40	100	SS	5.67	RFVP100
125	5"	EN 1092-1-PN40	125	SS	8.63	RFVP125
150	6"	EN 1092-1-PN40	150	SS	11.99	RFVP150

15	1/2"	ASTM 150 lbs	13	Steel	0.53	FVPA1013
20	3/4"	ASTM 150 lbs	19	Steel	0.78	FVPA1019
25	1"	ASTM 150 lbs	25	Steel	1.10	FVPA1025
32	1.1/4"	ASTM 150 lbs	32	Steel	1.46	FVPA1032
40	1.1/2"	ASTM 150 lbs	38	Steel	1.87	FVPA1038
40	1.1/2"	ASTM 150 lbs	40	Steel	1.87	FVPA1040*
50	2"	ASTM 150 lbs	50	Steel	2.84	FVPA1050
65	2.1/2"	ASTM 150 lbs	63	Steel	4.75	FVPA1063
65	2.1/2"	ASTM 150 lbs	65	Steel	4.75	FVPA1065*
80	3"	ASTM 150 lbs	75	Steel	5.48	FVPA1075
80	3"	ASTM 150 lbs	80	Steel	5.48	FVPA1080*
100	4"	ASTM 150 lbs	100	Steel	7.90	FVPA1100
125	5"	ASTM 150 lbs	125	Steel	10.77	FVPA1125
150	6"	ASTM 150 lbs	150	Steel	10.60	FVPA1150



Fixed flange: EN 1092-1 / type 11
 ASTM / A 182/ ANSI B16.5, ASA 150 lbs
 Assembly: HRRK swage ferrules, worm drive and band clamps
 SS = Stainless steel AISI 316 - EN 1.4401 / Steel = galvanized steel

FIXED FLANGE COUPLING WITH SERRATED HOSE SHANK AND COLLAR

ND	Inch	Flange pressure class	For hose mm	Material	Weight/pc kg	Reference
15	1/2"	ASTM 150 lbs	13	SS	0.75	RFVPA1013
20	3/4"	ASTM 150 lbs	19	SS	0.86	RFVPA1019
25	1"	ASTM 150 lbs	25	SS	1.20	RFVPA1025
32	1.1/4"	ASTM 150 lbs	32	SS	1.64	RFVPA1032
40	1.1/2"	ASTM 150 lbs	38	SS	1.97	RFVPA1038
40	1.1/2"	ASTM 150 lbs	40	SS	1.97	RFVPA1040*
50	2"	ASTM 150 lbs	50	SS	2.96	RFVPA1050
65	2.1/2"	ASTM 150 lbs	63	SS	4.81	RFVPA1063
65	2.1/2"	ASTM 150 lbs	65	SS	4.81	RFVPA1065*
80	3"	ASTM 150 lbs	75	SS	5.83	RFVPA1075
80	3"	ASTM 150 lbs	80	SS	5.83	RFVPA1080*
100	4"	ASTM 150 lbs	100	SS	8.55	RFVPA1100
125	5"	ASTM 150 lbs	125	SS	11.53	RFVPA1125
150	6"	ASTM 150 lbs	150	SS	15.24	RFVPA1150



Fixed flange: EN 1092-1 / type 11
 ASTM / A 182/ ANSI B16.5, ASA 150 lbs
 Assembly: HRRK swage ferrules, worm drive and band clamps
 SS = Stainless steel AISI 316 - 1.4401 / Steel = galvanized steel
 * available on request



FLANGE COUPLINGS



SMOOTH WELDING HOSE SHANK EN 14420-2 / DIN 2817

ND	Inch	Material	For hose mm	OD Ø welding end mm	Weight/pc kg	Reference
15	1/2"	Steel	13	21.3	0.04	FTU013
20	3/4"	Steel	19	26.9	0.05	FTU019
25	1"	Steel	25	33.7	0.09	FTU025
32	1.1/4"	Steel	32	42.4	0.11	FTU032
40	1.1/2"	Steel	38	48.3	0.15	FTU038
40	1.1/2"	Steel	40	48.3	0.15	FTU040*
50	2"	Steel	50	60.3	0.27	FTU050
65	2.1/2"	Steel	63	76.1	0.41	FTU063
65	2.1/2"	Steel	65	76.1	0.41	FTU065*
80	3"	Steel	75	88.9	0.56	FTU075
80	3"	Steel	80	88.9	0.59	FTU080*
100	4"	Steel	100	114.3	1.05	FTU100
125	5"	Steel	125	139.7	2.43	FTU125
150	6"	Steel	150	168.3	3.89	FTU150
200	8"	Steel	200	219.1	6.89	FTU200

15	1/2"	SS	13	21.3	0.05	RFTU013
20	3/4"	SS	19	26.9	0.06	RFTU019
25	1"	SS	25	33.7	0.10	RFTU025
32	1.1/4"	SS	32	42.4	0.14	RFTU032
40	1.1/2"	SS	38	48.3	0.17	RFTU038
40	1.1/2"	SS	40	48.3	0.17	RFTU040*
50	2"	SS	50	60.3	0.26	RFTU050
65	2.1/2"	SS	63	76.1	0.41	RFTU063
65	2.1/2"	SS	65	76.1	0.41	RFTU065*
80	3"	SS	75	88.9	0.63	RFTU075
80	3"	SS	80	88.9	0.66	RFTU080*
100	4"	SS	100	114.3	1.05	RFTU100
125	5"	SS	125	139.7	2.33	RFTU125
150	6"	SS	150	168.3	4.24	RFTU150
200	8"	SS	200	219.1	7.11	RFTU200



SS = Stainless steel AISI 316 - EN 1.4401 / Steel = non-galvanized steel

Assembly: RK and RKP safety clamps complying with EN 14420-3 / DIN 2817, FLEXOLINE® safety clamps

SERRATED WELDING HOSE SHANK

ND	Inch	Material	For hose mm	OD Ø welding end mm	Weight/pc kg	Reference
15	1/2"	Steel	13	21.3	0.05	FTP013
20	3/4"	Steel	19	26.9	0.07	FTP019
25	1"	Steel	25	33.7	0.09	FTP025
32	1.1/4"	Steel	32	42.4	0.13	FTP032
40	1.1/2"	Steel	38	48.3	0.15	FTP038
40	1.1/2"	Steel	40	48.3	0.15	FTP040*
50	2"	Steel	50	60.3	0.26	FTP050
65	2.1/2"	Steel	63	76.1	0.64	FTP063
65	2.1/2"	Steel	65	76.1	0.64	FTP065*
80	3"	Steel	75	88.9	0.56	FTP075
80	3"	Steel	80	88.9	0.61	FTP080*
100	4"	Steel	100	114.3	1.06	FTP100
125	5"	Steel	125	139.7	2.21	FTP125
150	6"	Steel	150	168.3	3.54	FTP150
200	8"	Steel	200	219.1	6.44	FTP200

15	1/2"	SS	13	21.3	0.05	RFTP013
20	3/4"	SS	19	26.9	0.07	RFTP019
25	1"	SS	25	33.7	0.09	RFTP025
32	1.1/4"	SS	32	42.4	0.13	RFTP032
40	1.1/2"	SS	38	48.3	0.17	RFTP038
40	1.1/2"	SS	40	48.3	0.17	RFTP040*
50	2"	SS	50	60.3	0.27	RFTP050
65	2.1/2"	SS	63	76.1	0.46	RFTP063
65	2.1/2"	SS	65	76.1	0.46	RFTP065*
80	3"	SS	75	88.9	0.55	RFTP075
80	3"	SS	80	88.9	0.59	RFTP080*
100	4"	SS	100	114.3	1.22	RFTP100
125	5"	SS	125	139.7	2.45	RFTP125
150	6"	SS	150	168.3	3.44	RFTP150
200	8"	SS	200	219.1	6.20	RFTP200

SS = Stainless steel AISI 316 - 1.4401 / Steel = non-galvanized steel
 Assembly: HRRK swage ferrules, worm drive and band clamps




FLANGE COUPLINGS



RAISED FACE GASKET FOR EN / DIN FLANGE - GORE™ UPG STYLE 800

ND	EN-DIN	OD Ø mm	ID Ø mm	Height mm	Colour	Reference
15	PN 10/40	51.0	22.0	3.0	White	FXG013DINRF
20	PN 10/40	61.0	27.0	3.0	White	FXG019DINRF
25	PN 10/40	71.0	34.0	3.0	White	FXG025DINRF
32	PN 10/40	82.0	43.0	3.0	White	FXG032DINRF
40	PN 10/40	92.0	49.0	3.0	White	FXG038DINRF
50	PN 10/40	107.0	61.0	3.0	White	FXG050DINRF
65	PN 10/40	127.0	77.0	3.0	White	FXG063DINRF
80	PN 10/40	142.0	89.0	3.0	White	FXG075DINRF
100	PN 10/16	162.0	115.0	3.0	White	FXG100DINRF
125	PN 10/16	192.0	141.0	3.0	White	FXG125DINRF
150	PN 10/16	218.0	169.0	3.0	White	FXG150DINRF
200	PN 10/16	273.0	220.0	3.0	White	FXG200DINRF




Seal colour is subject to change without prior notice

GORE™ Universal Pipe Seal Style 800 is a registered trademark of W.L. Gore & Associates, Inc.

RAISED FACE GASKET FOR EN / DIN FLANGE - novatec® PREMIUM II

ND	EN-DIN	OD Ø mm	ID Ø mm	Height mm	Colour	Reference
15	PN 10/40	51.0	22.0	2.0	Blue	FXN013DINRF
20	PN 10/40	61.0	27.0	2.0	Blue	FXN019DINRF
25	PN 10/40	71.0	34.0	2.0	Blue	FXN025DINRF
32	PN 10/40	82.0	43.0	2.0	Blue	FXN032DINRF
40	PN 10/40	92.0	49.0	2.0	Blue	FXN038DINRF
50	PN 10/40	107.0	61.0	2.0	Blue	FXN050DINRF
65	PN 10/40	127.0	77.0	2.0	Blue	FXN063DINRF
80	PN 10/40	142.0	89.0	2.0	Blue	FXN075DINRF
100	PN 10/16	162.0	115.0	2.0	Blue	FXN100DINRF
125	PN 10/16	192.0	141.0	2.0	Blue	FXN125DINRF
150	PN 10/16	218.0	169.0	2.0	Blue	FXN150DINRF
200	PN 10/16	273.0	220.0	2.0	Blue	FXN200DINRF



novatec® PREMIUM II is a registered trademark of Frenzelit

KEVLAR® is a registered trademark of Dupont Dow Elastomers

Seal colour is subject to change without prior notice