



## FLEXOLINE® SAFETY CLAMPS: ALUMINIUM

ND	For hose mm	OD hose min-max mm	Dimensions		Nuts and bolts		Weight/pc Kg	Reference
			Height mm	Width mm	Quantity	Thread metric		
25	25 x 5.0	34 - 36	50	69	4	M6	0.19	FRK025005
32	32 x 5.0	41 - 43	50	76	4	M6	0.28	FRK032005
40	38 x 5.0	47 - 49	50	83	4	M6	0.28	FRK038005
50	50 x 5.0	59 - 61	56	96	4	M8	0.38	FRK050005
65	63 x 6.0	74 - 76	74	117	4	M8	0.53	FRK063006
80	75 x 6.0	86 - 88	76	128	4	M8	0.58	FRK075006
100	100 x 6.5	112 - 114	120	166	4	M10	1.16	FRK100065



Production method: forging

Set of FLEXOLINE® safety clamps = one pair of clamps, nuts and bolts included

Bolts: DIN 912 / EN ISO 4762, zinc plated 10.9

Nuts: DIN 934 / EN ISO 4032, zinc plated 10.9

## FLEXOLINE® SAFETY CLAMPS: STAINLESS STEEL

ND	For hose mm	OD hose min-max mm	Dimensions		Nuts and bolts		Weight/pc Kg	Reference
			Height mm	Width mm	Quantity	Thread metric		
50	50 x 5.5	60 - 62	56	96	4	M8	0.38	FRKR050005
65	63 x 6.0	74 - 76	74	117	4	M8	0.53	FRKR063006
80	75 x 6.5	87 - 89	76	128	4	M8	0.58	FRKR075006



Production method: investment casting

Set of FLEXOLINE® safety clamps = one pair of clamps, nuts and bolts included

Bolts: DIN 912 / EN ISO 4762, stainless steel A.2 class 70

Nuts: DIN 934 / EN ISO 4032, stainless steel A.2 class 70