

'GK' COUPLINGS



'GK' COUPLING MALE THREADED

ND	Inch	Thread EN ISO 228-1	Material	Weight/pc Kg	Reference
10	3/8"	G 3/8	Brass Ms 58	0.07	GKM010
15	1/2"	G 1/2	Brass Ms 58	0.07	GKM013
20	3/4"	G 3/4	Brass Ms 58	0.07	GKM019
25	1"	G 1	Brass Ms 58	0.08	GKM025
32	1.1/4"	G 1.1/4	Brass Ms 58	0.10	GKM032
40	1.1/2"	G 1.1/2	Brass Ms 58	0.14	GKM038



Claw distance: 40 mm
 Working pressure: 10 bar / 145 psi
 Profiled seal: NBR standard
 Male thread: EN ISO 228-1, BSP

'GK' COUPLING FEMALE THREADED

ND	Inch	Thread EN ISO 228-1	Material	Weight/pc Kg	Reference
10	3/8"	G 3/8	Brass Ms 58	0.07	GKF010
15	1/2"	G 1/2	Brass Ms 58	0.07	GKF013
20	3/4"	G 3/4	Brass Ms 58	0.08	GKF019
25	1"	G 1	Brass Ms 58	0.08	GKF025
32	1.1/4"	G 1.1/4	Brass Ms 58	0.11	GKF032
40	1.1/2"	G 1.1/2	Brass Ms 58	0.13	GKF038



Claw distance: 40 mm
 Working pressure: 10 bar / 145 psi
 Seal: coupling side NBR standard
 thread side SBR
 Female thread: EN ISO 228-1, BSP

'GK' COUPLING WITH SERRATED HOSE SHANK

ND	Inch	For hose mm	Material	Weight/pc Kg	Reference
10	3/8"	10	Brass Ms 58	0.07	GKS010
13	1/2"	13	Brass Ms 58	0.07	GKS013
16	5/8"	16	Brass Ms 58	0.08	GKS016
19	3/4"	19	Brass Ms 58	0.08	GKS019
25	1"	25	Brass Ms 58	0.10	GKS025
32	1.1/4"	32	Brass Ms 58	0.14	GKS032
38	1.1/2"	38	Brass Ms 58	0.18	GKS038



Claw distance: 40 mm
 Working pressure: 10 bar / 145 psi
 Profiled seal: NBR standard
 Assembly: worm drive clamps or low pressure ferrules

'GK' COUPLINGS



'GK' COUPLING CAP

Material	Weight/pc Kg	Reference
Brass	0.09	GKK



Claw distance: 40 mm
Working pressure: 10 bar / 145 psi
Profiled seal: NBR standard
Cap without chain

SEAL

PROFILED SEAL

Material	Colour	OD Ø mm	ID Ø mm	Height mm	Box pieces	Weight kg	Reference
NBR	black	35.0	24.0	12.0	50	0.005	GKXB
FPM	green	35.0	24.0	12.0	50	0.009	GKXV

