

RMG series

Combine the best advantages of two couplings and you get a screw hose coupling that can be assembled with EN 14420-3 safety clamps, FLEXOLINE safety clamps, swage ferrules or band clamps. The hose shank of the male threaded RMG-couplings is slightly serrated and provided with a collar according to EN 14420-2.



EN 14420-3 and FLEXOLINE safety clamps



HRRK and HRRL swage ferrules



Band & worm drive clamps

According to EN 14420-5
Male threaded G EN ISO 228-1
Serrated hose shank + collar
Brass CW 614N
WP 25 bar
ND 15 - ND 100

RMG screw hose couplings	
Standard	EN 14420-5
Male thread	Flat sealing G EN ISO 228-1
Dimension	ND 15 - ND 100
Assembly	EN 14420-3 safety clamps FLEXOLINE safety clamps HRRK and HRRL swage ferrules Band & worm drive clamps
Finishing	Inner and outer surface machined Hexagon wrench surface
WP	PN 25
Material	Brass CW 614N

ND	For hose	OD Ø	Thread	Reference
15	13 mm	14 mm	G 1/2	RMG013
20	19 mm	20 mm	G 3/4	RMG019
25	25 mm	26 mm	G 1	RMG025
32	32 mm	33 mm	G 1.1/4	RMG032
40	38 mm	39 mm	G 1.1/2	RMG038
50	50 mm	51 mm	G 2	RMG050
65	63 mm	65 mm	G 2.1/2	RMG063
80	75 mm	76,1 mm	G 3	RMG075
100	100 mm	101,6 mm	G 4	RMG100