

SS SWAGE FERRULES HRRL



EA CRIMP COUPLING WITH SERRATED HOSE SHANK

| ND | For hose mm | OD Ø min. | OD Ø max. | Lenght | Reference |
|-----|--------------|-----------|-----------|--------|------------|
| 40 | 38 x 5 mm | 46,9 | 48,9 | 55 | HRRL038050 |
| 40 | 38 x 6,5 mm | 48,9 | 51,9 | 55 | HRRL038065 |
| 50 | 50 x 5,5 mm | 59,5 | 61,9 | 61 | HRRL050055 |
| 50 | 50 x 8 mm | 64 | 66,9 | 61 | HRRL050080 |
| 65 | 63 x 6 mm | 73,8 | 75,9 | 75 | HRRL065060 |
| 65 | 63 x 8 mm | 75,5 | 79,9 | 75 | HRRL065080 |
| 80 | 76 x 6,5 mm | 85,8 | 88,9 | 90 | HRRL075065 |
| 80 | 76 x 8 mm | 91,2 | 93,2 | 90 | HRRL075080 |
| 100 | 100 x 6,5 mm | 112,5 | 115,8 | 110 | HRRL100065 |
| 100 | 100 x 8 mm | 114,5 | 118,1 | 110 | HRRL100080 |



HRRL swage ferrules: stainless steel AISI 304 / 1.4301

Assembly: HRRL swage ferrules are recommended for the assembly of industrial rubber hoses.